

digi test Easy

EN

ASTM D1415 DIN ISO 48-2

Hardness tester for the "IRHD Normal" testing method for measuring the hardness of rubber, plastic, and all elastic materials with a minimum material thickness of 8 mm.







MEASURING METHODS

Our user-friendly hardness testing device digi test Easy offers you the ability to perform fully automated hardness tests using the IRHD N testing method. The digi test Easy combines the attractive price of the IRHD Compact with the comfort and automation of the digi test II.

The simple operation of the digi test Easy allow you to quickly measure your test specimens according to IRHD N. Get your measurement result at the push of a button.

IRHD N	



DIGITEST EASY

ΕN

ASTM D1415

ISO 48-2

KEY FEATURES



Fully automated hardness testing at an entry-level price. Thanks to the easy-to-use testing process, hardness measurements can be carried out effortlessly on your desired samples.



Proven technology – Made in Germany since 1954

The digi test Easy combines the attractive price of the IRHD Compact with the comfort and automation of the digi test II.



Automatically controlled lowering at standardized speed ensures consistent testing conditions for every application.



Minimal shipping effort for annual calibration

Simply send in the measuring unit of the digi test Easy – we'll take care of the rest.



Includesfree, Quick Measure "software tool

The free software allows you to easily capture, print, and export your data.



Available with ISO 17025 certification. We have been an accredited laboratory by DAkkS since 1996, following DIN EN ISO/IEC 17025:2018 standards.

TECHNICAL SPECIFICATIONS

Test stand with support arm	and measuring device	Voltage	100 – 250 VAC
Measurements (W x D x H)	min. 20 x 55 x 25 cm max. 20 x 60 x 31 cm	Current	2A
Electronic unit		Frequency	50 / 60 Hz
Measurements (W x D x H)) min. 26 x 11,5 x 26,5 cm max. 26 x 11,5 x 34 cm	Protection class	IP 30
Total weight	15 kg		



DIGITEST EASY

EN

ASTM D1415 DIN ISO 48-2

ACCESSORIES



Barofix Basic

Quick centering device for O-rings.



DAkkS accredited calibration certificate for the measuring device. The calibration

takes place according to DIN EN ISO/IEC 17025.



BareissOne Easy Software

for data collection and analysis





OVERVIEW







	digi test II	digi test Easy IRHD M	digi test Easy IRHD N
Shore (all methods)	✓	×	×
IRHD Micro	✓	✓	×
IRHD Normal	✓	×	✓
Interchangeable measuring devices	✓	×	×
Hysteresis (Software)	✓	×	×
Measuring table adjustable	✓	×	×
Barofix manual	✓	✓	✓
Barofix 4 (automatic)	✓	×	×
Quick Measure	✓	✓	✓
BareissOne (Full Version)	✓	×	×
BareissOne Easy (without Hysteresis Function)	×	✓	✓

Bareiss Prüfgerätebau GmbH

DAkkS-Kalibrierlaboratorium Breiteweg 1 89610 Oberdischingen, Germany Tel +49 (0) 7305 / 96 42-0 Fax +49 (0) 7305 / 96 42-22 sales@bareiss.de







MADE IN GERMANY SINCE 1954.





The accreditation is valid for the scope listed in certificate D-K-15206-01-00 (mechanical measurands in the range of hardness).